

## CLAIMS

SibAD

1. A sensed-pressure-data converter comprising:
- a pressure sensitive resistance element comprising:
- two insulating substrates disposed face to face; and
- 5 a pressure sensitive conductor interposed between said insulating substrates, for varying a resistance thereof according to a load applied from an outside of said insulating substrates;
- a controller for detecting an electric characteristic of said pressure sensitive resistance element, converting the electric
- 10 characteristic into a desired electric characteristic signal, and issuing a desired electric characteristic signal, comprising:
- an A/D converter receiving a signal from said pressure sensitive resistance element
- a memory preliminarily storing a compensation value
- 15 determined based on an error signal between the electric characteristic of said pressure sensitive resistance element and a reference electric characteristic; and
- a D/A converter compensating a signal from said A/D converter based on the electric characteristic of said pressure sensitive
- 20 resistance element due to a resistance change of said pressure sensitive resistance element based on the compensation value stored in said memory, and converting into a desired electric characteristic signal and issuing; and
- an adjustment value input terminal for inputting the error signal
- 25 into an input terminal of said A/D converter.

2. The sensed-pressure-data converter according to claim 1,

wherein said controller further comprises a temperature sensor for compensating suitably to an ambient temperature of said pressure sensitive resistance element.

- 5           3. The sensed-pressure-data converter according to claim 1 comprising a plurality of said pressure sensitive resistance elements, wherein said controller further comprises output terminals corresponding to the plurality of said pressure sensitive resistance elements, respectively.

Sub 13  
10           4. The sensed-pressure-data converter according to claim 1 further comprising:

a reference output voltage source for issuing a reference value of an offset of an output of said D/A converter; and

15           an error amplifier for receiving an output of said D/A converter and the reference value and for outputting the error signal.

20           5. The sensed-pressure-data converter according to claim 1, wherein said controller further comprises an abnormality detecting output terminal for detecting and outputting a signal showing an abnormality of a signal processing in said controller. 2

22